



*Pup trailers provide
many years of heavy hauling.*

Engineered for additional material hauling.

The J&J DynaHauler/PTA is built to handle a variety of demanding applications such as excavation, construction, mining and more. The frame is made of 12" by 30 lb. wide flange ex-ten 50 structural steel beam. The aluminum body is made of top grade materials and engineered to keep the trailer where it belongs - on the road.

Rely on our experience.

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 55+ years of experience to build you the dump trailers you want - we'll build them to your specification and application.

PUP TRAILER

DYNAHAULER

ISO 9001:2015 Certified.
Quality products,
quality workmanship.

*J&J Truck Bodies & Trailers
is a division of
Somerset Welding & Steel, Inc.*

**J&J TRUCK BODIES
& TRAILERS®**
Built for the Long Haul®

Call today! 800.777.2671
www.jjbodies.com

SPECIFICATIONS & DIMENSIONAL DATA FOR PUP TRAILERS



J&J pup trailers set the standard for quality and reliability.



Our tongues are built to handle your most demanding needs.

STANDARD SPECIFICATIONS*

- Nose:** Aerodynamically designed.
- Side Panels:** 54" high, 3/16" 5454-H34 with 6" top boards.
- Floor:** 1/4" 5454-H34 solid welded with radius corners
- Top Rail:** 4" x 4" x 3/16"
- Side & Rear Posts:** Extruded side posts 6061-T6 on 24" centers. Rear posts are 4" x 4" x 1/2" vertical angle, interlocked with rub rail, reinforced with formed 12" x 4" section.
- Understructure:** 4" I-beam cross-members on 15" centers 6061-T6. 6" x 6" x 3/8" aluminum angle long members 6061-T6.
- Tailgate:** 60" high, 3/16" 5454-H34, 3 panel.
- Lighting:** truck-Lite sealed and shock proof system.
- Axles:** Hendrickson 25,000 lb.
- Brakes:** 16 1/2" x 7" x 3/4" air operated ABS.

- Frame:** 12" x 30 lb. wide flange ex-ten 50 structural steel beam.
- Tongue:** 8" x 4" x 3/8" tube with hi-tensile reinforcing bar top & bottom of tube.
- Supension:** Reyco 21-B.
- Hoist:** A variety of front-mounted hoists are available, sized to fit body length and payload requirements.
- Rims:** 24.5 x 8.25.
- Tires:** 11R24.5, 14 ply, General Ameri-rib.
- Wheels:** Hub pilot disc.
- Landing Gear:** Holland 2 speed.
- Other Standard Features:** Mud guards & mud flaps - steps - shovel hangers - tarp bars.

PUP TRAILER DATA	
Lengths	Variable, consult your J&J Representative
Side Heights	54" to 72"
Overall Height	Variable, consult your J&J Representative*
Gate Height	54" to 72"
Frame to End of Floor	3"
Center of Hinge Pin to End of Floor	6"

*Standard specifications may vary according to customer's preferences and requirements. Many options available.
Call your J&J sales representative today!

*13'6" maximum available. Dimensions may vary slightly and are subject to change without notice.



D.O.T. Registered • A.S.M.E. Certified • National Board Registered

Distributed by:

ISO 9001:2015 Certified
 "Our Commitment to Quality"



10558 Somerset Pike
Somerset, PA 15501 USA
Phone: 814.444.3400
Fax: 814.443.2621
Toll Free: 800.777.2671 (USA only)
Email: sales@jjbodies.com
www.jjbodies.com